

03 Forklift / Truck

Tire size (inch)	Tread Design	Rim size	Tire weight		Tire Dimensions			
					Diameter +/- 3%		Max width +/- 3%	
			kg	lb	inch	mm	inch	mm
9.00-20	U	7.00-20	168.0	369.6	39.8	1010	8.7	220
	P				40.6	1030	10.2	260
14/65-20	P	10.00-20	228.0	501.6	40.6	1030	13.2	336
10.00-20 7.5"	D	7.50-20	171.0	377.0	40.9	1040	9.8	248
	S		160.0	352.7	40.9	1040	9.4	240
	P		171.0	377.0	40.9	1040	9.3	235
10.00-20 8.0"	D	8.00-20	171.0	377.0	40.9	1040	10.0	253
	U		171.0	377.0	41.3	1050	9.7	247
11.00-20 7.5"	D	7.50-20	188.0	414.5	41.3	1050	10.6	270
	U		201.0	443.1	42.9	1090	10.8	275
11.00-20 8.0"	D	8.00-20	188.0	414.5	41.3	1050	10.6	270
	U		201.0	443.1	42.9	1090	10.8	275
12.00-20 8.0"	U	8.00-20	201.0	443.1	42.9	1090	10.8	275
	D		224.0	493.8	43.3	1100	11.3	286
12.00-20 8.5"	D	8.50-20	234.0	515.9	43.3	1100	11.3	286
	U		250.0	551.2	45.3	1150	11.3	287
	P		260.0	573.2	45.3	1150	11.8	300
13.00-20	MD	10.00-20	268.0	589.6	43.3	1100	12.7	322
14.00-20	MD	10.00-20	376.0	827.2	49.2	1250	13.8	350
12.00-24	U	8.50-24	271.0	596.2	48.8	1240	11.8	300
	H				48.6	1235	12.6	320
	P				48.8	1240	12.6	320
14.00-24	D	10.00-24	427.0	939.4	53.5	1360	14.2	360
	H				55.7	1415	15.0	380
	P				53.6	1361	14.1	359
14.00-25	D	10.00-25	417.0	917.4	53.5	1360	14.2	360
17.5-25	D, D1A, D2A	14.00-25	515.0	1133.0	53.4	1356	17.3	440
	P				53.5	1360	18.1	461
16.00-25	D	11.25-25	672.0	1478.4	59.1	1500	16.9	430
	P, P1A, P2A				59.5	1512	16.9	430
18.00-25	D	13.00-25	860.0	1892.0	63.8	1620	19.3	490
	P				62.6	1590	18.9	480
	P ULTRA		1175.0	2585.0	68.9	1750	19.7	500
21.00-25	P	16.00-25	1335.0	2943.0	68.9	1750	22.7	576

04 Other Special Vehicles

Tire size (inch)	Tread Design	Rim size	Tire weight		Tire Dimensions			
					Diameter +/- 3%		Max width +/- 3%	
			kg	lb	inch	mm	inch	mm
10.00-20 7.5"	D1A	7.50-20	164.0	360.8	40.9	1040	9.8	248
10.00-20 8.0"	D1A	8.00-20	164.0	360.8	40.9	1040	9.8	248
355/50-20	P, P1A	10.00-20	126.0	277.2	33.6	853	12.4	315
385/65-24	F, F1A, F2A	10.00-24	207.0	455.4	42.1	1070	14.6	370
41X17-24	F, F1A, F2A	15.00-24	225.0	495.0	41.0	1041	17.0	432
445/65-24	F, F2A	12.00-24	311.0	684.2	45.3	1150	17.3	440
42X12-24	U	8.50-24	171.0	376.2	41.0	1042	11.8	300
43X16-20	MD	13.00-20	328.4	724.1	43.0	1092	15.7	398
44X18-20	U	14.00-20	327.0	719.4	42.1	1069	18.0	457
48X14-24	U	10.00-24	324.0	712.8	48.4	1230	13.6	345
51X14-24	D	10.00-24	406.0	895.1	51.0	1310	14.1	360
53X18-24	MD	14.00-24	565.0	1245.0	53.0	1346	18.0	457
45X20.5-25	U	17.00-25	390.0	860.0	45.0	1143	20.5	520
	MH		366.0	807.1	45.0	1143	20.5	520
49X17.5-25	P	14.00-25	450.0	992.0	49.0	1245	17.5	444
49X20.5-25	MH	17.00-25	504.0	1108.8	49.0	1245	20.5	520
52X20.5-25	D, D1A	17.00-25	615.0	1353.0	53.1	1350	20.3	516
52X27-25	D	22.00-25	850.0	1870.0	53.1	1350	27.0	685
26.5-25	XD	22.00-25	1440.0	3175.0	69.1	1755	26.4	670
	XP		1540.0	3395.0				
29.5-25	XP	25.00-25	1920.0	4224.0	73.6	1870	29.5	750
58X32-47	R	30.00-47	570.0	1254.0	58.0	1474	32.2	819
18.00-33	U, U2A	13.00-33	990.0	2178.0	72.5	1842	18.0	458
21.00-35	U2A	15.00-35	1605.0	3531.0	81.6	2072	22.5	572
24.00-35	U, U2A	17.00-35	1786.0	3929.2	81.6	2072	25.6	650
63X18-37	D	13.00-37	740.0	1631.4	63.0	1600	19.3	490
61X38-37	P	33.00-37	1321.0	2912.8	61.0	1550	38.0	965
29.5-45	MD, MD1A	22.00-45	1835.0	4037.0	79.6	2022	30.5	775
35/50-45	MD, MD1A	28.00-45	1975.0	4345.0	80.0	2032	35.0	890
35/45-51	MD, MD1A	28.00-51	1975.0	4345.0	82.3	2090	35.0	890
45/45-63	U1A	32.00-63	4350.0	9570.0	106.3	2700	45.0	1143